



Image depicts 12x12 inch section. Shown railroaded.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Vicente Rainfall

Category: Upholstery

Material: Polyester/Polyester Blend

Physical Properties

Content: 100% Polyester

Finish: PFAS-free spill- and stain-resistant treatment

Backing: Acrylic

Width: 54"

Weight: 28.00 oz per linear yards

Repeat: 29.125" H x 20.375" V

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant -
Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4; Wet: Grade 3

Breaking Strength: ASTM D5034 - Warp: 217 lbs; Weft: 470 lbs

Seam Slippage: ASTM D4034 - Warp: 91 lbs; Weft: 44 lbs

Abrasion: 100,000* double rubs, Wyzenbeek

Tear Strength: ASTM D2261 - Warp: 40.0 lbs; Weft: 73.0 lbs

Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 40 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based
agent; a diluted bleach solution can be used

Sustainability

Product contains 52% post-consumer recycled content

Product contains 48% pre-consumer recycled content

Free of conflict minerals, flame-retardant chemicals, PFAS/PFOA/PFOS,
phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), PFAS

*Actual Wyzenbeek test results: 105,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.