



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Kinetic
Chestnut

Category: Upholstery
Material: Polyester/Polyester Blend

Physical Properties

Content: 100% Polyester
Width: 54"
Weight: 20.80 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC
Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4; Wet: Grade 3
Breaking Strength: ASTM D5034 - Warp: 323.1 lbs; Weft: 119.3 lbs
Seam Slippage: ASTM D4034 - Warp: 64.3 lbs; Weft: 48.3 lbs
Abrasion: 72,000 double rubs, Wyzenbeek
Tear Strength: ASTM D2261 - Warp: 53.0 lbs; Weft: 53.0 lbs
Pilling: ASTM D3511 (Brush Pill) - Grade 4
Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 40 hours
Cleaning Code: W = Clean with only a waterbased cleaning agent

Sustainability

Free of conflict minerals, flame-retardant chemicals, heavy metals, PFAS/PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents