



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Carmel Flint

Category: Upholstery

Material: Cotton/Cotton Blend

Physical Properties

Content: 51% Cotton
49% Polyester

Finish: Aquaclean® PFAS-free repel-and-release technology

Width: 55"

Weight: 27.90 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant -
Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5

Breaking Strength: ASTM D5034 - Warp: 30.9 lbs; Weft: 19.8 lbs

Seam Slippage: ASTM D4034 - Warp: 47.4 lbs; Weft: 50.9 lbs

Abrasion: 100,000 double rubs, Wyzenbeek; 90,000 cycles, Martindale

Tear Strength: ASTM D2261 - Warp: 46.2 lbs; Weft: 33.6 lbs

Pilling: ASTM D4970 (Martindale) - Class 5

Pilling: ASTM D3511 (Brush Pill) - Grade 4

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 40 hours

Cleaning Code: W = Clean with only a waterbased cleaning agent

Sustainability

Free of conflict minerals, heavy metals, PFAS/PFOA/PFOS, phthalates
(BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents, PFAS