




Image depicts 12x12 inch section. Shown railroaded.
© 2024 Wolf-Gordon Inc. All Rights Reserved

Merrion
TAN

Category: Upholstery

Material: Vinyl

Physical Properties

Content: 100% Vinyl

Finish: PFAS-free spill- and stain-resistant treatment

Backing: Polyester Knit

Width: 54"

Weight: 30.75 oz per linear yards

Performance

For Indoor/Outdoor Use: Antimicrobial, mildew resistant, and water repellent

Flame Resistance: Passes Cal TB 117-2013, with flame retardant -
Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4; Wet: Grade 4.5

Breaking Strength: ASTM D751 - Warp: 100 lbs; Weft: 79 lbs

Marine Applications: IMO FTP Code 2010

Abrasion: 100,000 double rubs, Wyzenbeek

Coating Adhesion: ASTM D751 - Warp: 3.0 lbs; Weft: 3.0 lbs

Tear Strength: ASTM D2261 - Warp: 10.0 lbs; Weft: 13.0 lbs

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 1100 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Sustainability

Free of flame-retardant chemicals, formaldehyde, heavy metals, PVC, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP)

Printed with solvent-free inks