



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Nova

Elm

Category: Upholstery

Material: Polyurethane Silicone

Physical Properties

Content: 90% Polyurethane
10% Silicone

Finish: Graffiti-Proof, PFAS-free, stain-and ink-resistant treatment

Backing: Polyester

Width: 54"

Weight: 21.00 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant -
Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5

Marine Applications: IMO A 652 (16) 8.2

Abrasion: 100,000* double rubs, Wyzenbeek

Tear Strength: ASTM D2261 - Warp: 6.2 lbs; Weft: 5.8 lbs

Seam Strength: ASTM D751- Warp: 101.9 lbs; Weft: 102.0 lbs

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 200 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Sustainability

Free of PFAS/PFOA/PFOS, PVC, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents

Printed with solvent-free inks

*Actual Wyzenbeek test results: 500,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.