



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Marl SAND

Category: Upholstery

Material: Polyester/Polyester Blend

Physical Properties

Content: 100% Polyester

Finish: Spill- and stain-resistant treatment

Backing: Styrene-butadiene Rubber

Width: 54"

Weight: 19.00 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4.5; Wet: Grade 4.5

Seam Slippage: ASTM D4034 - Warp: 88.6 lbs; Weft: 82.4 lbs

Abrasion: 100,000 double rubs, Wyzenbeek

Tear Strength: ASTM D2261 - Warp: 56.6 lbs; Weft: 59.3 lbs

Pilling: ASTM D3511 (Brush Pill) - Grade 4.5

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 40 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent

Sustainability

Free of halogenated flame retardants, heavy metals, lead, PFAS/PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents

Printed with solvent-free inks