



© 2024 Wolf-Gordon Inc. All Rights Reserved

Heath Sterling

Category: Upholstery

Material: Polyester/Polyester Blend Supreen

Physical Properties

Content: 88% Polyester

7% Acrylic

3% Polyurethane

2% Silicone

Finish: Supreen PFAS-free, stain-resistant treatment with moisture barrier

Width: 54"

Weight: 24.50 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Class 4.5

Breaking Strength: ASTM D5034 - Warp: 308 lbs; Weft: 221 lbs

Seam Slippage: ASTM D4034 - Warp: 113 lbs; Weft: 124 lbs

Abrasion: 100,000 double rubs, Wyzenbeek

Tear Strength: ASTM D2261 - Warp: 28.2 lbs; Weft: 28.5 lbs

Pilling: ASTM D3511 (Brush Pill) - Class 4.5

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 40 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Sustainability

Free of conflict minerals, flame-retardant chemicals, heavy metals, PFAS/PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP)

Printed with solvent-free inks