



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

Tallinn

RAPIDS

Category: Upholstery

Material: Polycarbonate Polyurethane

Physical Properties

Content: 100% Polyurethane

Finish: Inherently PFAS free, stain- and ink-resistant, liquid impermeable treatment

Backing: Polyester Knit

Width: 54"

Weight: 20.00 oz per linear yards

Performance

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 5; Wet: Grade 5

Breaking Strength: ASTM D751 - Warp: 109 lbs; Weft: 127 lbs

Abrasion: 100,000 double rubs, Wyzenbeek

Coating Adhesion: ASTM D751 - Warp: 8.8 lbs; Weft: 7.1 lbs

Tear Strength: ASTM D2261 - Warp: 7.0 lbs; Weft: 6.3 lbs

Seam Strength: ASTM D751- Warp: 59.9 lbs; Weft: 57.4 lbs

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 200 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Hydrolysis Resistance: ISO 1419 - 5 weeks

Sustainability

Low emitting-passes Cal 01350 standard (LEED EQ 4.2)

Free of conflict minerals, heavy metals, PFAS/PFOA/PFOS, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP)

Printed with solvent-free inks