



Image depicts 12x12 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

## Amagansett SAND

Category: Upholstery

Material: Polyester/Polyester Blend

### Physical Properties

---

Content: 91% Polyester

8% Cotton

1% Nylon

Finish: Spill- and stain-resistant treatment

Backing: Acrylic

Width: 58"

Weight: 17.48 oz per linear yards

### Performance

---

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4; Wet: Grade 3

Breaking Strength: ASTM D5034 - Warp: 268 lbs; Weft: 277 lbs

Seam Slippage: ASTM D4034 - Warp: 50 lbs; Weft: 65 lbs

Abrasion: 51,000 double rubs, Wyzenbeek

Pilling: ASTM D3511 (Brush Pill) - Grade 5

Colorfastness to Light: Passes AATCC 16 - Grade 4 @ 40 hours

Cleaning Code: S = Clean only with a water-free dry cleaning solvent

### Sustainability

---

Product contains 28.0% post-consumer recycled content

Product contains 34.0% pre-consumer recycled content

Free of phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents