



Image depicts 8x8 inch section.

© 2024 Wolf-Gordon Inc. All Rights Reserved

## Ansonia

### PAPAYA

Category: Upholstery

Material: Polyurethane

#### Physical Properties

---

Content: 100% Polyurethane

Finish: PFAS-free spill- and stain-resistant treatment

Backing: Polyester

Width: 54"

Weight: 16.50 oz per linear yards

#### Performance

---

Flame Resistance: Passes Cal TB 117-2013, AB 2998 compliant - Passes NFPA 260/UFAC

Wet and Dry Crocking: Passes AATCC 8 - Dry: Grade 4.5; Wet: Grade 4.5

Breaking Strength: ASTM D751 - Warp: 125 lbs; Weft: 117 lbs

Seam Slippage: ASTM D4034 - Warp: 48 lbs; Weft: 47 lbs

Abrasion: 100,000\* double rubs, Wyzenbeek

Colorfastness to Light: Passes AATCC 16 - Grade 5 @ 200 hours

Cleaning Code: W-S = Clean with either a water- or solvent-based agent; a diluted bleach solution can be used

Hydrolysis Resistance: ISO 1419 - 5 weeks

#### Sustainability

---

Low emitting-passes Cal 01350 standard (LEED EQ 4.2)

Free of flame-retardant chemicals, phthalates (BBP, DBP, DEHP, DIDP, DINP, DnHP, DnOP), solvents

Printed with solvent-free inks

\*Actual Wyzenbeek test results: 250,000 double rubs without showing wear. Please note that actual Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.